


MLF1005G1R5JT000













Size	
Length(L)	1.00mm ±0.05mm
Width(W)	0.50mm ±0.05mm
Thickness(T)	0.50mm ±0.05mm
Recommended Land Pattern (A)	0.50mm Nom.
Recommended Land Pattern (B)	0.40mm Nom.
Recommended Land Pattern (C)	0.50mm Nom.

Electrical Characteristics		
Inductance	1.5μH ±5% at 10MHz	
Rated Current (L Change) [Typ.]		
Rated Current (L Change) [Max.]		
Rated Current (Temperature Rise) [Typ.]		
Rated Current (Temperature Rise) [Max.]	35mA	
DC Resistance [Typ.]	680mΩ	
DC Resistance [Max.]	950mΩ	
Self Resonant Frequency [Min.]	100MHz	
Self Resonant Frequency [Typ.]	200MHz	
Q [Min.]	30	
Q [Typ.]	60	

Other	
Operating Temp. Range (Including Self-Temp. Rise)	-55 to 125°C
Soldering Method	Reflow
	Iron Soldering
AEC-Q200	No
Packing	Punched (Paper)Taping [180mm Reel]
Package Quantity	10000pcs
Weight	0.0012g

[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



MLF1005G1R5JT000













Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)









[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.



MLF1005G1R5JT000










Associated Images



[!] Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.