

Medical PSU FSP090-RHCM1 / FSP090-RHBM1

DESCRIPTION

Power supply can deliver 90W continuous output power. High efficiency & compact dimension with an IEC320/C8 (FSP090-RHCM1) or IEC320/C6 (FSP090-RHBM1) inlet to mate with interchangeable cord for world-wide use.

APPLICATION

Display, Electrocardiogram (ECG), Respirator

FEATURES

- Input voltage range 85~264VacSlim design 140 * 71 * 22 mm

- Slim design 140 * 71 * 22 mm
 High altitude 5000M operation
 Meet EN 55011 / EN 55022 and FCC class B emission
 OVP, OCP, OTP protection
 Compliant with Energy Star efficienct level V
- * No load power consumption less than 0.5W
- * Avergy active efficiency greater than 87%
- Optional output connectors

WATTAGE

Wattage: 90W

DIMENSION

Dimension: 140mm(L) x 71mm(W) x

22mm(H)

INPUT SPECIFICATION

90-264 Vac 47-63 Hz Input Range: Input Frequency:

Leakage Current: 100 uA @ 264Vac / 63 Hz SAFETY STANDARD APPAOVAL

(€

ENVIRONMENTAL SPECIFICATION

Operating Temperature:0°C to +40°C TEMP.Range:

Storage Temperature: -20 °C to +

85℃

Humidity: Operating: 5% to 95% RH, Non-

condensing

OUTPUT ELECTRICAL

12 V/ 7.5 A Single Output: Line Regulation: +/- 1% Load Regulation:

This content is subject to change, please refer to specification for more detail. FSP reserve the right to change the content without prior notice