


RECOMMEND P.C.B. LAYOUT



CIRCUIT: SPDT

CONTACT CONFIGURATION

| ▲ SWITCH FUNCTION | | |
|-------------------|--------|--------|
| POS. 1 | POS. 2 | POS. 3 |
| DN | NONE | DN |
| 2-3 | OPEN | 2-1 |

- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. RATING: 5A @ 120VAC OR 28VDC;
2A @ 250VAC
 5. ▲ DENOTES CRITICAL PARAMETER

| REV. | ECN NO. | DESCRIPTION | DATE | CHKD |
|------|---------|-------------------------|---------|------|
| B | 15154 | CHANGED DIMENSION | 8/8/05 | PV |
| A | 12823 | RELEASED FOR PRODUCTION | 2/21/03 | RC |

| | | | | | | | | | | | |
|--------------------|--|-------|--|---------|--|----|--|---------|--|-----|--|
| TITLE | | SCALE | | DATE | | DR | | DWG | | REV | |
| 300AWSP1JIBLKVS2QE | | NONE | | 2/21/03 | | RC | | T301027 | | B | |



THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED