



WR-90 Flexible Waveguide Twist With a CPR-90G Flange Operating From 8.2 GHz to 12.4 GHz

Waveguide Twists Technical Data Sheet

PE-W90TF006-36

Features

- Thirty six inch long WR-90 waveguide
- Twistable
- Flexes in both the E and H plane
- Neoprene sleeve allows pressurization
- 8.2 GHz to 12.4 GHz Frequency Range
- Brass flanges with a silver plating

Applications

- Simplifies positioning of reflectors for line microwave radio links.
- Test Benches
- Eliminates installation problems caused by misalignment.
- Allows expansion/contraction due to thermal issues.
- Pressurized waveguide systems
- Provides vibration isolation
- Microwave Radio

Description

The PE-W90TF006-36 is part of Pasternack's family of flexible waveguide. The waveguide body is made of a helically wound silver plated copper in both E and H planes without impairing VSWR or attenuation. The waveguide is covered by a neoprene jacket which protects the waveguide, provides mechanical support and allows the waveguide to be pressurized.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	8.2		12.4	GHz
VSWR		1.07:1		
Insertion Loss		0.45		dB

Mechanical Specifications

Waveguide Size	WR-90
Waveguide Design	Twistable
Section Length	36 in [914.4 mm]
E-Plane Minimum Bend Radius	205 in [5180 mm]
E-Plane Minimum Bend Radius, 10° offset	254 mm
H-Plane Minimum Bend Radius	50 in [1270 mm]
H-Plane Minimum Bend Radius, 20° offset	508 mm
Maximum Offset Rotation, One side	90 degrees/ft
Maximum Offset Rotation, Repetitive	24 degrees/ft
Maximum Operating Pressure	45 psig


Click the following link (or enter part number in "SEARCH" field) to view price, inventory and technical data for Waveguide Twist With a CPR-90G Flange Operating From 8.2 GHz to 12.4 GHz PE-W90TF006-36



WR-90 Flexible Waveguide Twist With a CPR-90G
Flange Operating From 8.2 GHz to 12.4 GHz

Waveguide Twists Technical Data Sheet

PE-W90TF006-36



WR-90 Flexible Waveguide Twist With a CPR-90G Flange Operating From 8.2 GHz to 12.4 GHz. Pasternack Enterprises has same day shipment for this product and are committed to maintain a 99% availability and are part of the broadest selection of waveguide products.

Click the following link (or enter part number in "SEARCH" inventory and select the product): [WR-90 Flexible Waveguide Twist With a CPR-90G PE-W90TF006-36](http://www.pasternack.com/wr-90-flexible-waveguide-twist-pe-w90tf006-36)

URL: <http://www.pasternack.com/wr-90-flexible-waveguide-twist-pe-w90tf006-36>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE-W90TF006-36 CAD Drawing


WR-90 Flexible Waveguide Twist With a CPR-90G Flange
Operating From 8.2 GHz to 12.4 GHz



PASTERNAK
PE-W90TF006-36

CPR 90G	Dimension	Inches	mm
A		0.400	10.16
B		0.900	22.86
C		2.092	53.14
D		1.652	41.96
E		0.624	15.85
F		1.592	40.44
G		0.626	15.90
H		1.152	29.26

0.170 ϕ
[4.3] THRU
(8 HOLES)



DWG TITLE

PE-W90TF006-36

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

FSCM NO. 53919

CAD FILE 100115

SCALE N/A

SIZE A

2233

(PE) PASTERNAK®
THE ENGINEER'S RF SOURCE
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com