



SAW Components

BAW/SAW Duplexer

WCDMA Band II

Series/type:	B8078
Ordering code:	B39202B8078P810
Date:	February 13, 2015
Version:	2.7

© EPCOS AG 2015. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

EPCOS AG is a TDK Group Company.

Data Sheet

Characteristics

Temperature range for specification:	T = -20 °C to +85 °C
ANT terminating impedance:	Z _{ANT} = 50 Ω
RX terminating impedance:	Z _{RX} = 100 Ω (balanced) 10nH
TX terminating impedance:	Z _{TX} = 50 Ω

Characteristics TX - ANT		min.	typ. @ 25°C	max.	
Center frequency	f _C	—	1880.0	—	MHz
Maximum insertion attenuation					
@f _{Carrier} 1852.4 ... 1907.6 MHz	α _{WCDMA} ¹⁾	—	2.0	3.0	dB
@f _{Carrier} 1852.4 ... 1907.6 MHz	α _{WCDMA} ¹⁾	—	2.0	2.5 ³⁾	dB
Error Vector Magnitude					
@f _{Carrier} 1852.4 ... 1907.6 MHz	EVM ²⁾	—	1.0	3.0	%
@f _{Carrier} 1852.4 ... 1907.6 MHz	EVM ²⁾	—	1.0	2.0 ³⁾	%
Input VSWR (TX port)					
1850.0 ... 1910.0 MHz		—	1.5	2.0	
Output VSWR (ANT port)					
1850.0 ... 1910.0 MHz		—	1.5	2.0	
Attenuation	α				
10.0 ... 728.0 MHz		30	33	—	dB
728.0 ... 764.0 MHz		30	33	—	dB
869.0 ... 894.0 MHz		30	34	—	dB
1574.0 ... 1577.0 MHz		36	42	—	dB
1577.0 ... 1680.0 MHz		30	42	—	dB
@f _{Carrier} 1932.4 ... 1987.6 MHz	α _{WCDMA} ¹⁾	45	50	—	dB
2110.0 ... 2155.0 MHz		35	44	—	dB
2400.0 ... 2500.0 MHz		25	30	—	dB
3690.0 ... 3830.0 MHz		20	25	—	dB
5150.0 ... 5350.0 MHz		16	23	—	dB
5540.0 ... 5860.0 MHz		16	22	—	dB

¹⁾ Attenuation of WCDMA signal ("Powertransferfunction"). Please refer to annotation on page (6).

²⁾ Error Vector Magnitude (EVM) based on definition given in 3GPP TS 25.141.

³⁾ Valid for room temperature 25 °C

Data Sheet

Characteristics

Temperature range for specification:	T = -20 °C to +85 °C
ANT terminating impedance:	Z _{ANT} = 50 Ω
RX terminating impedance:	Z _{RX} = 100 Ω (balanced) 10nH
TX terminating impedance:	Z _{TX} = 50 Ω

Characteristics ANT-RX		min.	typ. @ 25°C	max.	
Center frequency	f _C	—	1960.0	—	MHz
Maximum insertion attenuation					
@f _{Carrier}	1932.4 ... 1987.6MHz α _{WCDMA} ¹⁾	—	3.0	3.7	dB
@f _{Carrier}	1932.4 ... 1987.6MHz α _{WCDMA} ¹⁾	—	3.0	3.5 ²⁾	dB
Error Vector Magnitude					
@f _{Carrier}	1932.4 ... 1987.6MHz EVM ³⁾	—	1.8	6.0	%
@f _{Carrier}	1932.4 ... 1987.6MHz EVM ³⁾	—	1.8	3.5 ²⁾	%
@f _{Carrier}	1932.4 ... 1987.6MHz EVM ³⁾	—	1.8	2.8 ⁴⁾	%
Input VSWR (ANT port)					
	1930.0 ... 1990.0MHz	—	1.8	2.6	
Output VSWR (RX port)					
	1930.0 ... 1990.0MHz	—	1.8	2.4	
Attenuation					
	1.0 ... 1765.0MHz α	30	46	—	dB
	1835.0 ... 1850.0MHz	30	58	—	dB
@f _{Carrier}	1852.4 ... 1907.6MHz α _{WCDMA} ¹⁾	45	56	—	dB
	2025.0 ... 2050.0MHz	10	28	—	dB
	2050.0 ... 2075.0MHz	25	36	—	dB
	2400.0 ... 2484.0MHz	30	54	—	dB
	2810.0 ... 2910.0MHz	30	58	—	dB
	3775.0 ... 3905.0MHz	30	60	—	dB
	5625.0 ... 5815.0MHz	30	61	—	dB
	2075.0 ... 6000.0MHz	30	37	—	dB

¹⁾ Attenuation of WCDMA signal ("Powertransferfunction"). Please refer to annotation on page (6).

²⁾ Valid only for reduced temperature range from 0 °C to 85 °C.

³⁾ Error Vector Magnitude (EVM) based on definition given in 3GPP TS 25.141.

⁴⁾ Valid for room temperature 25 °C

Data Sheet

Characteristics

Temperature range for specification:	T = -20 °C to +85 °C
Antenna terminating impedance:	Z _{ANT} = 50 Ω
RX terminating impedance:	Z _{RX} = 100 Ω (balanced) 10nH
TX terminating impedance:	Z _{TX} = 50 Ω

Characteristics ANT - RX		min.	typ. @ 25 °C	max.	
Common mode suppression	S_{cs21}				
1930.0 ... 1990.0 MHz		23	28	—	dB
IMD Product Level Limits¹⁾					
at f_{TX}=1880MHz, f_{RX}=1960MHz					
Blocker 1	80.0 MHz	—	-98	—	dBm
Blocker 2	1800.0 MHz	—	-107	—	dBm
Blocker 3	3840.0 MHz	—	-102	—	dBm

¹⁾ IMD product level limits for power levels P_{TX}=21.5dBm (antenna port output power) and P_{Blocker}=-15dBm (antenna port input power)

Characteristics TX - RX		min.	typ. @ 25 °C	max.	
Isolation	α				
@f _{Carrier} 1852.4 ... 1907.6 MHz	$\alpha_{WCDMA}^{1)}$	50	58	—	dB
@f _{Carrier} 1932.4 ... 1987.6 MHz	$\alpha_{WCDMA}^{1)}$	46	51	—	dB
Common Mode Isolation	α				
@f _{Carrier} 1852.4 ... 1907.6 MHz	$\alpha_{WCDMA}^{1)}$	46	50	—	dB

¹⁾ Attenuation of WCDMA signal ("Powertransferfunction"). Please refer to annotation on page (6).


Maximum ratings

Operable temperature range ¹⁾	T	-30/+85	°C	machine model, 10 pulses human body model, 1 pulse, field induced charged device model, 3 pulses, source and load impedance 50 Ω } continuous wave T = 55°C, 50.000 h
Storage temperature range	T _{stg}	-40/+85	°C	
DC voltage	V _{DC}	5.5	V	
ESD voltage	V _{ESD}	50 ²⁾	V	
	V _{ESD}	100 ³⁾	V	
	V _{ESD}	500 ⁴⁾	V	
Input power at 1850.0 ... 1910.0 MHz elsewhere	P _{IN}	29	dBm	
		10	dBm	

1) Defines the temperature range in which the BAW / SAW device keeps its typical characteristics, however the specification values are not valid for the extended range..

2) acc. to JESD22-A115B (machine model), 10 negative & 10 positive pulses.

3) acc. to JESD22-A114F (human body model), 1 negative & 1 positive pulses.

4) acc. to JESD22-C101C (field induced charged device model), 3 negative & 3 positive pulses.



Annotation for characteristics section

Attenuation of WCDMA signal ("Powertransferfunction", α_{WCDMA}) is determined by

$$\int_{-\infty}^{\infty} |S_{\text{ds21}}(f) H_{\text{RRC}}(f - f_{\text{Carrier}})|^2 df$$

f_{Carrier} according to 3GPP TS 25.101 (e.g. for WCDMA Band 2 Passband, f_{Carrier} ranges from 1852.4 MHz (lowest Tx channel) to 1907.6 MHz (highest Tx channel)). $H_{\text{RRC}}(f)$ is the transfer function of the root-raised cosine transmit pulse shaping filter according to 3GPP TS 25.101 with the following normalization:


$$\int_{-\infty}^{\infty} |H_{\text{RRC}}(f)|^2 df = 1$$


Frequency Response TX-ANT (PTF)

Frequency Response TX-ANT (wideband)



Data Sheet



Frequency Response ANT-RX (PTF)




Frequency Response ANT-RX (wideband)






Frequency Response TX-ANT Passband (PTF)




Frequency Response ANT-RX Passband (PTF)






Frequency Response TX-RX (PTF)




Frequency Response Tx-Rx (PTF) Common Mode Isolation



Data Sheet





Frequency Response RX-ANT Common Mode Suppression









VSWR TX-port



VSWR RX-port (differential mode)



VSWR ANT-port



SAW Components	B8078
BAW/SAW Duplexer	1880.0 / 1960.0 MHz

Data Sheet



Type	B8078
Ordering code	B39202B8078P810
Marking and package	C61157-A8-A48
Packaging	F61074-V8247-Z000
Date codes	L_1126
S-parameters	B8078_NB_UN.s4p (unmatched, nearby) B8078_WB_UN.s4p (unmatched, wideband) see file header for port/pin assignment table
Soldering profile	S_6001
RoHS compatible	RoHS-compatible means that products are compatible with the requirements according to Art. 4 (substance restrictions) of Directive 2011/65/EU of the European Parliament and of the Council of June 8 th , 2011, on the restriction of the use of certain hazardous substances in electrical and electronic equipment ("Directive") with due regard to the application of exemptions as per Annex III of the Directive in certain cases.
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.
Matching coils	See Inductor pdf-catalog http://www.tdk.co.jp/tefe02/coil.htm#aname1 and Data Library for circuit simulation http://www.tdk.co.jp/etvcl/index.htm

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG
Systems, Acoustics, Waves Business Group
P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2015. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CeraLink, CeraPlas, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FilterCap, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, TFAP, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.